

Button Cell Expert, Extra Capacity and Long Lasting

Alkaline Manganese Battery Cell					
Model No.	Size (mm) Ø x H	Nominal Voltage	Nominal Capacity	Weight (g)	SUB.
LR-621	6.8 x 2.1	1.5V	15 mAh	0.30	AG-1
LR-726	7.9 x 2.6	1.5V	27 mAh	0.38	AG-2
LR-41	7.9 x 3.6	1.5V	43 mAh	0.64	AG-3
LR-626	6.8 x 2.6	1.5V	22 mAh	0.34	AG-4
LR-754	7.9 x 5.4	1.5V	68 mAh	0.90	AG-5
LR-921	9.5 x 2.1	1.5V	26 mAh	0.55	AG-6
LR-927	9.5 x 2.7	1.5V	45 mAh	0.64	AG-7
LR-1120	11.6 x 2.0	1.5V	44 mAh	0.86	AG-8
LR-936	9.5 x 3.6	1.5V	62 mAh	0.88	AG-9
LR-1130	11.6 x 3.0	1.5V	80 mAh	1.20	AG-10
LR-721	7.9 x 2.1	1.5V	20 mAh	0.38	AG-11
LR-43	11.6 x 4.2	1.5V	115 mAh	1.60	AG-12
LR-44	11.6 x 5.4	1.5V	160 mAh	2.00	AG-13



100% Computerize Full Check



Button Battery Automatic Prouction Line

Automotive Production and Imported Material Suitable for Computer Mother Board, Remote Control, Electronic Flash Light, Electronic Dictionary, Toys, Calculator, Watch, Clock, and other Electronic Devices.



Assembling Of Lithium Battery



Computerize Code Marking



Coin Type Lithium Manganese Battery							
Model No.	Size (mm) Ø x H	Nominal Voltage	Nominal Capacity	Standard Current	Continuous Current (Max.)	Pulse Current (Max.)	Weight (g)
CR-927	9.5 x 2.7	3V	30 mAh	0.1 mA	0.2 mA	5 mA	0.5
CR-1216	12.5 x 1.6	3V	25 mAh	0.1 mA	0.2 mA	5 mA	0.7
CR-1220	12.5 x 2.0	3V	38 mAh	0.1 mA	0.2 mA	5 mA	0.9
CR-1225	12.5 x 2.5	3V	50 mAh	0.1 mA	0.2 mA	5 mA	1.0
CR-1616	16.0 x 1.6	3V	50 mAh	0.1 mA	0.4 mA	8 mA	1.2
CR-1620	16.0 x 2.0	3V	70 mAh	0.1 mA	0.4 mA	8 mA	1.3
CR-2016	20.0 x 1.6	3V	80 mAh	0.1 mA	0.5 mA	10 mA	1.8
CR-2025	20.0 x 2.5	3V	155 mAh	0.2 mA	0.6 mA	15 mA	2.5
CR-2032	20.0 x 3.2	3V	220 mAh	0.2 mA	0.6 mA	15 mA	3.1
CR-2320	23.0 x 2.0	3V	130 mAh	0.2 mA	0.8 mA	15 mA	3.0
CR-2330	23.0 x 3.0	3V	260 mAh	0.2 mA	0.8 mA	15 mA	4.0
CR-2430	24.5 x 3.0	3V	280 mAh	0.2 mA	1 mA	15 mA	4.2
CR-2450	24.5 x 5.0	3V	550 mAh	0.2 mA	1 mA	15 mA	6.2

Various kind of Spot-welding tag or pin available for industrial purpose.

Carrying ISO 9001 - Management System, Quality is Guaranteed

Zinc-Chloride Battery (Extra Heavy Duty) 0.% Mercury & Cadmium						
Model No.	Jacket	Size (mm) Ø x H	Nominal Voltage	Nominal Capacity	Weight (g)	SUB.
R1P	PVC	11 x 30.0	1.5V	340 mAh	6	N, SUM5
R03P	PVC	10 x 44.5	1.5V	200 mAh	9	AAA, SUM4
R6P	Metal	14 x 50.0	1.5V	450 mAh	20.8	AA, SUM3
R6P	PVC	14 x 50.0	1.5V	450 mAh	17.5	AA, SUM3
R14P	Metal	25 x 50.0	1.5V	2800 mAh	40	C, SUM2
R20P	Metal	33 x 61.0	1.5V	5900 mAh	83	D, SUM1



Cylindrical Battery Production Line



Extra Heavy Duty



Alkaline Battery

Alkaline Manganese Dioxide Battery 0.% Mercury & Cadmium						
Model No.	Jacket	Size (mm) Ø x H	Nominal Voltage	Nominal Capacity	Weight (g)	SUB.
LR03	Aluminium Foil	10 x 44.5	1.5V	1050 mAh	11.5	AAA, AM-4
LR06	Aluminium Foil	14 x 50.0	1.5V	2500 mAh	23	AA, AM-3
LR14	Aluminium Foil	25 x 50.0	1.5V	7500 mAh	71	C, AM-22
LR20	Aluminium Foil	33 x 61.0	1.5V	16000 mAh	143	D, AM-1



Battery Testing Lab



Computerize Plastic Injection

Latest Technology, Automotive Production, Long Lasting and Powerful, High Temperature Model Available.

High Voltage Battery (0.% Mercury)						
Model No.	Jacket	Size (mm) L x W	Nominal Voltage	Nominal Capacity	Weight (g)	SUB.
9V	Metal	48.5 x 26.5	9V	330 mAh	37	6F-22
23A	Metal	Ø10 x 28.3	12V	55 mAh	8.1	LRV08, MN21
27A	Metal	Ø7.8 x 27.3	12V	25 mAh	4.6	L828



World First 0% Hg 23A, 27A-12V Battery



23A, 27A-12V Battery Both Mercury Free and Standard Types are Available



6F22 9V Battery Production Workshop



New Leader Mercury Free Button Battery fully complied with RoHS (Pb, Hg, Cd, Cr6+, PBBs, PBDEs) directives.